



MAC PLANTMASTER ELECTRIC

MAC
INTERNATIONAL
PREMIER DEALER

Electrically Heated Static Pressure Washer

- 80°C with market leading heat retention
- 375lt stainless steel lagged water tank
- High quality steel cabinet with all standard Plantmaster cabinet features
- Larger water tank and increased heating power gives a longer run time with constant heat



KEY SPECIFICATION

80°C Maximum Heat

11lt-18lt/min Water Flow

18kw-48kw Heating Powder

120-200bar Pressure

400v, 32amp Minimum
Power Supply





HUGH CRANE
(Cleaning Equipment) Limited

MAC PLANTMASTER ELECTRIC



DESIGNED & BUILT TO MEET THE DEMANDS OF THE NEW MARKETPLACE, WHERE ELECTRICALLY HEATED MACHINES ARE REQUIRED. ESPECIALLY FOR FOOD APPLICATIONS, HOWEVER GROWING INTO ALL MARKETPLACES

STANDARD FEATURES

- Low rewing 1450rpm pump & motor
- High temperature Interpump
- Unique stainless steel subframe construction
- Easy access for servicing
- Double insulated hot water tank
- Low thermal loss in standby
- Maximum temperature output 80°C
- Digital temperature display
- Simple 24v controls
- Available from 18-48kw heating power
- Lockable powder coated steel front door
- Hinged and removable cabinet front door and lid

CABINET FINISH

- Powder coated steel cabinet with lockable controls
- High quality matte paint finish
- Zinc phosphate steel pre-treatment for weather proofing



MAC
ELECTRIC

18/24
DESIGN

OPTIONAL ACCESSORIES AVAILABLE

THE MAC 18/24 MACHINE DESIGNED TO RUN ON A STANDARD 32AMP POWER SUPPLY - **INNOVATION IN TECHNOLOGY**

	PLANTMASTER E1	PLANTMASTER E2	PLANTMASTER E3	PLANTMASTER E4	PLANTMASTER E5	PLANTMASTER E6	PLANTMASTER E7
Water Flow	11lt per minute	13lt per minute	13lt per minute	15lt per minute	13lt per minute	15lt per minute	18lt per minute
Pressure	120bar	170bar	170bar	200bar	170bar	200bar	160bar
Motor Specification	3kW, 4hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm
Heating Power	18-24kW	24Kw	36Kw	36Kw	48Kw	48Kw	48Kw
Volts Amps Watts	400v/32A/22Kw	400v/45A/29.5Kw	400v/63A/41.5Kw	400v/63A/41.5Kw	400v/80A/41.5Kw	400v/80A/41.5Kw	400v/80A/41.5Kw
Shutdown System	Timed total stop	Timed total stop	Timed total stop	Timed total stop	Timed total stop	Timed total stop	Timed total stop
Max. Temperature	80°C	80°C	80°C	80°C	80°C	80°C	80°C
Weight	250kg	250kg	250kg	250kg	250kg	250kg	250kg
Dimensions (h x w x d)	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm

Acle: 01493 750072
Peterborough: 01733 206991
Stamford: 01778 381700

sales@hughcrane.co.uk
www.hughcrane.co.uk



HUGH CRANE
(Cleaning Equipment) Limited

MAC
INTERNATIONAL
PREMIER DEALER