

High Pressure Cleaner

Cold water, mobile - Series 3x3



KD923-F UK

Food appliance

with stainless steel pump,
hot water resistant



Type		KD923-F UK-Standard	KD923-F UK-Premium
Voltage	3/PE/AC/50Hz/415V	<ul style="list-style-type: none"> ▶ 10m HP-Hose DN08 - 315bar blue ▶ Trigger-Gun with swivel ▶ Double Spray-Lance 900 mm c/w Nozzle-Protection ▶ Stainless-Steel Jet-Nozzle 25° ▶ 15l Cleaning-Detergent tank ▶ Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	<ul style="list-style-type: none"> ▶ Hose-Reel ▶ 15m HP-Hose DN08 - 315bar blue ▶ Trigger-Gun with swivel ▶ Double Spray-Lance 900 mm c/w Nozzle-Protection ▶ High and low pressure jet nozzle 25° ▶ Soft Foam Kit with 2 l foam detergent tank ▶ 17l Water-Storage tank ▶ Water-Supply separation acc. water reg. ▶ Chemical supply in high-pressure Jet c/w Metering-valve
Operating pressure	30-100bar/3-10MPa		
Max. pressure	120bar/12MPa		
Discharge capacity	300-840l/h		
Nozzle size	070		
Max. Inlet temperature	80°C		
Pump speed	1400rpm		
Connected load	3,1kW/13A		
Electrical protection	13A slow-blowing		
Weight net/with package		54kg/74kg	58kg/78kg
Dimensions device/with package (LxWxH)		805x485x950mm/790x595x810mm	830x485x950mm/790x595x810mm
<p>Food appliance with abrasion resistant high pressure hose blue, self-supporting, robust, corrossions free, rotation-moulded device-chassis for food industry, stainless steel, impact-resistant device-cover made of ABS, triplex-piston pump with chrome, nickel plated pump head (hot water resistant), high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar stainless steel.</p>			
Art. No.		445001	445002
Retail price plus VAT		£3,049.00	£3,483.00