



SAFETY DATA SHEET

TAR AND BITUMEN REMOVER

1. IDENTIFICATION OF THE SUBSTANCE AND SUPPLIER

Product Name: Tar and bitumen remover
Identified Uses: Cleaning agent.
Supplied By: Hugh Crane (Cleaning Equipment) Ltd
South Walsham Road, Acle
Norwich NR13 3ES
Contact Telephone: Tel 01493 750072 Fax 01493 751854

2. HAZARDS IDENTIFICATION

Signal word: Danger
Hazard Symbols:



Hazard Statements:
H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H413: May cause long lasting harmful effects to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	EINECS	CAS	Content	Classification
White Spirit	265-191-7	64742-88-7	75-100 %	H226, H304, H315, H413
Toluene	203-625-9	108-88-3	10-25%	H226, H304, H315
Anionic Surfactant Emulsifier	284-664-9	84961-74-0	<1%	H315

4. FIRST AID MEASURES

Inhalation: Move the exposed person to fresh air at once. Keep the affected person warm and at rest.
Ingestion: Give plenty of water to drink and seek medical advice. DO NOT INDUCE VOMITING.
Skin contact: Wash with soap and water. Remove contaminated clothing.
Eye contact: Irrigate the eye thoroughly with plenty of clean water, and seek medical advice.

5. FIRE FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires. Do not use water jet.
Exposure hazards: Hazardous combustion products may include carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

Ventilate the area. Eliminate all sources of ignition. Contain spillages with sand or other absorbent media. Small spillages and residues may be flushed away with plenty of water. Do not allow product to enter drains or water courses.

7. HANDLING AND STORAGE

Usage precautions: Use in a well ventilated area. Avoid breathing vapours. Avoid contact with skin and eyes.
Storage: Store at moderate temperatures in a dry, well ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

O E S	8 Hour TWA	S.T.E.L.
Aliphatic Hydrocarbon	100 ppm	Not set

Recommended Safety Equipment

Eye Protection: Safety goggles or face shield.
Hand Protection: Solvent resistant gloves.
Skin Protection: Overalls and safety shoes/boots.
Respiratory Protection: Not applicable in normal use. Provide adequate general and local exhaust ventilation.



HUGH CRANE

— Cleaning Equipment Limited —

South Walsham Road, Acle, Norwich NR13 3ES
Telephone: 01493 750072 Fax: 01493 751854
Email: sales@hughcrane.co.uk
Website: www.hughcrane.co.uk

Tar and Bitumen Remover Page 2 of 2
SDS Revision Date 13/08/2014 Reviewed 05/11/2020
Print Date 22/12/2020

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear to straw coloured liquid.
Odour: Solvent
pH Value: Not applicable
Flash Point: 30°C (approx.)
Relative Density: Approx 0.810 @ 20°C (Water = 1.000)
Water solubility: Partially miscible.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.
Reactivity: Avoid contact with strong oxidants such as liquid chlorine and concentrated oxygen.
Hazardous Reactions: Carbon oxides may be released during thermal decomposition.

11. TOXICOLOGICAL INFORMATION

Harmful if swallowed. Minute amounts aspirated into the lungs by ingestion or vomiting may cause pulmonary injury. Prolonged contact may cause skin irritation. May cause transient irritation if eye contact occurs.

12. ECOLOGICAL INFORMATION

This product does not contain any PBT or vPvB substances. Not readily biodegradable. May cause long-term adverse effects in the aquatic environment if released in large quantities.

13. DISPOSAL CONSIDERATION

Dispose of through a licensed waste operator.

14. TRANSPORT INFORMATION

ADR/CDG Class: 3, FLAMMABLE
Transport label hazard symbol:



U.N. No: 1993
Shipping name: Flammable liquid, n.o.s. (contains solvent naphtha)
Packing Group: III

15. REGULATORY INFORMATION

Labelling according to EU requirements:



Hazard symbols: H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H413: May cause long lasting harmful effects to aquatic life.
Precautionary statements: P102: Keep out of the reach of children
P301+310: IF SWALLOWED: Immediately call a doctor or physician
P302+352: IF ON SKIN: Wash with soap and water
P305+351: IF IN EYES: Rinse continuously with water for several minutes

16. OTHER INFORMATION

The contents of hazardous ingredients listed in section 3 are expressed as a percentage range of active matter calculated on a weight/volume basis unless otherwise specified.
The ingredients used in this product, where applicable, are registered under the REACH system with the European Chemicals Agency (ECHA).

SDS Revision Date: 13th August 2014.
SDS Reviewed: 5th November 2020

Legal disclaimer: The foregoing information is based on the state of our knowledge and experience of the product and the various materials used in the preparation. It is in good faith, but no warranty is implied. Buyers must satisfy themselves as to the suitability of the product and take responsibility for making their own assessments.

End of Safety Data Sheet.



SAFETY DATA SHEET

TAR AND BITUMEN REMOVER

1. IDENTIFICATION OF THE SUBSTANCE AND SUPPLIER

Product Name: Tar and bitumen remover
Identified Uses: Cleaning agent.
Supplied By: Hugh Crane (Cleaning Equipment) Ltd
South Walsham Road, Acle
Norwich NR13 3ES
Contact Telephone: Tel 01493 750072 Fax 01493 751854

2. HAZARDS IDENTIFICATION

Signal word: Danger

Hazard Symbols:



Hazard Statements:
H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H413: May cause long lasting harmful effects to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	EINECS	CAS	Content	Classification
White Spirit	265-191-7	64742-88-7	75-100 %	H226, H304, H315, H413
Toluene	203-625-9	108-88-3	10-25%	H226, H304, H315
Anionic Surfactant Emulsifier	284-664-9	84961-74-0	<1%	H315

4. FIRST AID MEASURES

Inhalation: Move the exposed person to fresh air at once. Keep the affected person warm and at rest.
Ingestion: Give plenty of water to drink and seek medical advice. DO NOT INDUCE VOMITING.
Skin contact: Wash with soap and water. Remove contaminated clothing.
Eye contact: Irrigate the eye thoroughly with plenty of clean water, and seek medical advice.

5. FIRE FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires. Do not use water jet.
Exposure hazards: Hazardous combustion products may include carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

Ventilate the area. Eliminate all sources of ignition. Contain spillages with sand or other absorbent media. Small spillages and residues may be flushed away with plenty of water. Do not allow product to enter drains or water courses.

7. HANDLING AND STORAGE

Usage precautions: Use in a well ventilated area. Avoid breathing vapours. Avoid contact with skin and eyes.
Storage: Store at moderate temperatures in a dry, well ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

O E S	8 Hour TWA	S.T.E.L.
Aliphatic Hydrocarbon	100 ppm	Not set

Recommended Safety Equipment

Eye Protection: Safety goggles or face shield.
Hand Protection: Solvent resistant gloves.
Skin Protection: Overalls and safety shoes/boots.
Respiratory Protection: Not applicable in normal use. Provide adequate general and local exhaust ventilation.



HUGH CRANE

— Cleaning Equipment Limited —

South Walsham Road, Acle, Norwich NR13 3ES
Telephone: 01493 750072 Fax: 01493 751854
Email: sales@hughcrane.co.uk
Website: www.hughcrane.co.uk

Tar and Bitumen Remover Page 2 of 2
SDS Revision Date 13/08/2014 Reviewed 05/11/2020
Print Date 22/12/2020

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear to straw coloured liquid.
Odour: Solvent
pH Value: Not applicable
Flash Point: 30°C (approx.)
Relative Density: Approx 0.810 @ 20°C (Water = 1.000)
Water solubility: Partially miscible.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.
Reactivity: Avoid contact with strong oxidants such as liquid chlorine and concentrated oxygen.
Hazardous Reactions: Carbon oxides may be released during thermal decomposition.

11. TOXICOLOGICAL INFORMATION

Harmful if swallowed. Minute amounts aspirated into the lungs by ingestion or vomiting may cause pulmonary injury. Prolonged contact may cause skin irritation. May cause transient irritation if eye contact occurs.

12. ECOLOGICAL INFORMATION

This product does not contain any PBT or vPvB substances. Not readily biodegradable. May cause long-term adverse effects in the aquatic environment if released in large quantities.

13. DISPOSAL CONSIDERATION

Dispose of through a licensed waste operator.

14. TRANSPORT INFORMATION

ADR/CDG Class: 3, FLAMMABLE
Transport label hazard symbol:



U.N. No: 1993
Shipping name: Flammable liquid, n.o.s. (contains solvent naphtha)
Packing Group: III

15. REGULATORY INFORMATION

Labelling according to EU requirements:



Hazard symbols: H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H413: May cause long lasting harmful effects to aquatic life.

Precautionary statements: P102: Keep out of the reach of children
P301+310: IF SWALLOWED: Immediately call a doctor or physician
P302+352: IF ON SKIN: Wash with soap and water
P305+351: IF IN EYES: Rinse continuously with water for several minutes

16. OTHER INFORMATION

The contents of hazardous ingredients listed in section 3 are expressed as a percentage range of active matter calculated on a weight/volume basis unless otherwise specified.
The ingredients used in this product, where applicable, are registered under the REACH system with the European Chemicals Agency (ECHA).

SDS Revision Date: 13th August 2014.
SDS Reviewed: 5th November 2020

Legal disclaimer: The foregoing information is based on the state of our knowledge and experience of the product and the various materials used in the preparation. It is in good faith, but no warranty is implied. Buyers must satisfy themselves as to the suitability of the product and take responsibility for making their own assessments.

End of Safety Data Sheet.