

SC2000

The productivity of a ride-on with the footprint of a walk-behind





Easy to operate: Extremely user friendly and intuitive dashboard with One-Touch button integrated in the steering wheel



Filling system with automatic shut off when tank is full (optional)



Easy to clean - recovery tank lid is completely removable

# Riding high on cleaning efficiency

## Easy fast and productive cleaning

The Nilfisk SC2000 micro ride-on scrubber dryer eases the working effort significantly compared a walk-behind machine. An attractive choice for cleaning of offices, supermarkets, sports centres, shops, restaurants, hotels, and institutions like hospitals and schools.

With a working speed of up to 6 km/h – from an average 4 km/h of a walk-behind scrubber dryer– the SC2000 has a positive impact on both productivity and cleaning costs.

The SC2000 is easy to manoeuvre even in narrow spaces thanks to its compact dimensions. A silent mode function for ultra-low sound level makes the machine suitable for daytime cleaning, even in sound sensitive areas.

Downtime is also minimised through the 2-key system: 1 grey key for the operator with basic settings and 1 yellow key for super user with full options setting to prevent any errors by the operator.

- Productive: High speed (6 km/h), 70/70 L tanks and 3.5 hours of running time
- Effective: 53 cm scrubbing width and powerful suction on all types of floors
- Consistent cleaning quality: Solution flow of detergent/ water automatically controlled by speed allowing consistent cleaning result whilst optimising water and detergent
- Powerful: Double pressure function to clean very dirty areas and whenever required
- Low energy consumption: brush motor with speed control depending on floor condition
- User-friendly: Automatic deck and squeegee raising/ lifting by pressing the One-Touch button and Click on/off button to easily install and remove the brush/pad holder
- Easy handling: Light squeegee with patented elastic strap system to easily remove and change blades



Recovery tank fully tiltable to give easy access to battery compartment and Ecoflex system



USB port as optional





# Reliability is also our mantra when it comes to service

A Nilfisk machine functions optimally when cared for by regular service and maintenance visits. Therefore we have created the optimal service solution: three levels of service reflecting different requirements and an optional supply of a substitute machine in critical situations.

## Service Solutions Standard – Professional maintenance

Your contract encompasses two yearly maintenance visits and 48 hours response time. Breakdown visits and spare parts are billed separately.

## Service Solutions Plus – Optimised performance

With the Plus solution you have a firm grip on your maintenance and repair costs while knowing that your performance is never compromised, only optimised.

## Service Solutions Premium – Maximised uptime

If uptime is your absolute top priority and key concern, Service Solutions Premium is the best choice. A quarterly maintenance visit is included, and there are no sudden financial surprises.

Electric actuators for lowering/ raising the deck and the squeegee by pushing a button

2 key system with separate setting controls for the Superuser and the Operator

Automatic squeegee lifting in reverse

Protective bumpers on brush deck and squeegee to absorb shocks.



Robust and chemical resistant polyethylene tanks

Easy access to operator's seat from both sides; ergonomic working position and foot pedal comfortably placed

Ecoflex system allows flexible detergent settings and water-only cleaning. 60 second burst of power to increase water, detergent and scrub pressure when needed.

Brush click-off/on button for easy installation and removal of brush/pad holder

## Technical specifications

Description	Unit	SC2000	SC2000 Full package
Item no.		9087360020	9087364020
Voltage	V	24	24
Rated power	W	450	450
Sound pressure level	dB(A)	68/62 ±3	68/62 ±3
Productivity rate theoretical/ actual	m²/h	3180/2230	3180/2230
Scrubbing width	mm	530	530
Solution/recovery tank	litre	70/70	70/70
Brush/pad diameter	mm	530/508	530/508
Brush pressure	kg	15/30	15/30
Brush speed	rpm	155	155
Battery compartment size (lxwxh)	mm	350x360x280	350x360x280
Length x width x height	cm	127x55x102	127x55x102
Weight (machine only)	kg	155	228
Operating weight	kg	342	342
<b>FEATURES:</b>			
Squeezable drain hose with flow control		●	●
Debris cage		●	●
On-Board Charger		○	●
Battery		○	●

● = Standard feature  
○ = Optional feature

## Nilfisk Ltd.

Nilfisk House · Bowerbank Way · Gilwilly Industrial Estate · Penrith · Cumbria · CA11 9BQ  
Tel.: 01768 868995 (UK) · 01 2943838 (IE)  
Email: mail.uk@nilfisk.com (UK) · info.ie@nilfisk.com (IE)  
www.nilfisk.co.uk · www.nilfisk.ie

