

SAFETY DATA SHEET
FABRIC UPHOLSTERY CLEANER

Page: 1

Compilation date: 23/08/2005

Revision date: 26/09/2016

Revision No: 5

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FABRIC UPHOLSTERY CLEANER

Product code: FCL500

Synonyms: FABRIC CLEANER

FCL500

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Specialised Aerosols Company Limited

Carr Green Lane

Mapplewell

Barnsley

South Yorkshire

S75 6DY

Tel: 01226 387101

Fax: 01226 387100

Email: sales@specialised-aerosols.co.uk

1.4. Emergency telephone number

Emergency tel: 07836317118

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Flam. Aerosol 1: H222

Most important adverse effects: Extremely flammable aerosol. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H319: Causes serious eye irritation.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



Signal words: Danger

SAFETY DATA SHEET

FABRIC UPHOLSTERY CLEANER

Page: 2

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PROPANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%

PHOSPHATE ESTER

-	72283-31-9	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315	<1%
---	------------	---	---	-----

ALCOHOLS,C12-14,ETHOXYLATED91-2,5 EO), SULFATES, SODIUM SALTS

500-234-8	68891-38-3	-	Skin Irrit. 2: H315; Eye Dam. 1: H318	<1%
-----------	------------	---	---------------------------------------	-----

ISOBUTANE

200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	<1%
-----------	---------	--	-------------------------------------	-----

BUTANE

203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	<1%
-----------	----------	--	-------------------------------------	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water.

Inhalation: Not applicable.

[cont...]

SAFETY DATA SHEET

FABRIC UPHOLSTERY CLEANER

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

[cont...]

SAFETY DATA SHEET
FABRIC UPHOLSTERY CLEANER

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PROPANE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1800 mg/m ³	7200 mg/m ³	-	-

ISOBUTANE

UK	2400 mg/m ³	9600 mg/m ³	-	-
----	------------------------	------------------------	---	---

BUTANE

UK	1450 mg/m ³	1810 mg/m ³	-	-
----	------------------------	------------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Typical.

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Flammability limits %: lower: 0.8

upper: 9.0

Flash point°C: -10

[cont...]

SAFETY DATA SHEET
FABRIC UPHOLSTERY CLEANER

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain.
The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

[cont...]

SAFETY DATA SHEET
FABRIC UPHOLSTERY CLEANER

Page: 6

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Empty containers must not be burned because of explosion hazard.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

[cont...]

SAFETY DATA SHEET
FABRIC UPHOLSTERY CLEANER

Page: 7

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.
H222: Extremely flammable aerosol.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.