



SAFETY DATA SHEET

GRAFFITI REMOVER

Page: 1

Compilation date: 23/08/2005

Revision date: 02/11/2021

Revision No: 6

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: GRAFFITI REMOVER

Product code: GRR500

Synonyms: GRR500

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Specialised Aerosols Company Limited

Carr Green Lane

Mapplewell

Barnsley

South Yorkshire

S75 6DY

Tel: 01226 387101

Fax: 01226 387100

Email: sales@specialised-aerosols.co.uk

1.4. Emergency telephone number

Emergency tel: 07836317118

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; STOT SE 3: H336; Aquatic Chronic 3: H412; -: EUH208; -: H229

Most important adverse effects: Contains cinnamal (I). May produce an allergic reaction. Extremely flammable aerosol.
Pressurised container: May burst if heated. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains cinnamal (I). May produce an allergic reaction.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

[cont...]

SAFETY DATA SHEET

GRAFFITI REMOVER

Page: 2



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P222: Do not allow contact with air.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P271: Use only outdoors or in a well-ventilated area.
P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.
P501: Dispose of contents/container to in accordance with local regulations.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

1-METHOXY-2-PROPANOL

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|----------|-----------|-------------------------------------|---------|
| 203-539-1 | 107-98-2 | - | Flam. Liq. 3: H226; STOT SE 3: H336 | 50-70% |

PROPANE

| | | | | |
|-----------|---------|--|-------------------------------------|-------|
| 200-827-9 | 74-98-6 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 1-10% |
|-----------|---------|--|-------------------------------------|-------|

BUTANE

| | | | | |
|-----------|----------|--|-------------------------------------|-------|
| 203-448-7 | 106-97-8 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 1-10% |
|-----------|----------|--|-------------------------------------|-------|

PROPAN-2-OL

| | | | | |
|-----------|---------|---|---|-----|
| 200-661-7 | 67-63-0 | - | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336 | <1% |
|-----------|---------|---|---|-----|

ISOBUTANE

| | | | | |
|-----------|---------|--|-------------------------------------|-----|
| 200-857-2 | 75-28-5 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | <1% |
|-----------|---------|--|-------------------------------------|-----|

[cont...]

SAFETY DATA SHEET

GRAFFITI REMOVER

Page: 3

CINNAMAL (L)

| | | | | |
|-----------|----------|---|---|-----|
| 203-213-9 | 104-55-2 | - | - | <1% |
|-----------|----------|---|---|-----|

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

[cont...]

SAFETY DATA SHEET

GRAFFITI REMOVER

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

1-METHOXY-2-PROPANOL

Workplace exposure limits:

Respirable dust:

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|-----------------------|-----------------------|------------|--------------|
| UK | 375 mg/m ³ | 560 mg/m ³ | - | - |

PROPANE

| | | | | |
|----|------------------------|------------------------|---|---|
| UK | 1800 mg/m ³ | 7200 mg/m ³ | - | - |
|----|------------------------|------------------------|---|---|

BUTANE

| | | | | |
|----|------------------------|------------------------|---|---|
| UK | 1450 mg/m ³ | 1810 mg/m ³ | - | - |
|----|------------------------|------------------------|---|---|

PROPAN-2-OL

| | | | | |
|----|-----------------------|------------------------|---|---|
| UK | 999 mg/m ³ | 1250 mg/m ³ | - | - |
|----|-----------------------|------------------------|---|---|

ISOBUTANE

| | | | | |
|----|------------------------|------------------------|---|---|
| UK | 2400 mg/m ³ | 9600 mg/m ³ | - | - |
|----|------------------------|------------------------|---|---|

DNEL/PNEC Values

DNEL / PNEC No data available.

[cont...]

SAFETY DATA SHEET

GRAFFITI REMOVER

Page: 5

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Slightly soluble

Flammability limits %: lower: 0.8

upper: 11.5

Flash point°C: -10

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

[cont...]

SAFETY DATA SHEET

GRAFFITI REMOVER

Page: 6

11.1. Information on toxicological effects

Hazardous ingredients:

1-METHOXY-2-PROPANOL

| | | | | |
|-----|-----|------|-------|-------|
| IVN | RAT | LD50 | 4200 | mg/kg |
| ORL | MUS | LD50 | 11700 | mg/kg |
| ORL | RAT | LDLO | 3739 | mg/kg |

PROPAN-2-OL

| | | | | |
|-----|-----|------|------|-------|
| IVN | RAT | LD50 | 1088 | mg/kg |
| ORL | MUS | LD50 | 3600 | mg/kg |
| ORL | RAT | LD50 | 5045 | mg/kg |
| SCU | MUS | LDLO | 6 | gm/kg |

Relevant hazards for product:

| Hazard | Route | Basis |
|----------------------|-------|-----------------------|
| STOT-single exposure | - | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

[cont...]

SAFETY DATA SHEET

GRAFFITI REMOVER

Page: 7

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Empty containers must not be burned because of explosion hazard.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

[cont...]

SAFETY DATA SHEET

GRAFFITI REMOVER

Page: 8

Phrases used in s.2 and s.3: EUH208: Contains cinnamal (l). May produce an allergic reaction.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]