

6000 SERIES

STANDARD FEATURES

- PTO Drive Shaft & Guard
- Choice of Triplex Ceramic Plunger Pump
- Proportional Flow Unloader & Pressure Gauge
- 90 Metre (300ft) Capacity Manual Hose Reel
- Large Capacity Inlet Filter
- 1500 Gallon Capacity Water Tank
- Removable Drawbar Jack
- Low Level Filling Port & Coupling
- Manhole Inspection Hatch
- Access Ladder
- Brakes
- Road Lights
- Safety Valve
- Quick Release Gun allows Tools to be Interchanged
- 75 Metre (240') Two Wire 1/2" High Pressure Hose
- 1.0 Metre Single Lance
- Fully Adjustable Pressure



Smaller bowzers available



OPTIONAL ACCESSORIES

- Recirculating Anti-freeze System
- Chemical Injector
- Foam Application Equipment
- Sand Blasting Equipment
- Drain Jetting Hoses & Jets
- Insulated Frost Cover
- Hydraulic Hose Reel Rewind
- Inlet Hose Reel

The Commando 6000 Series with a large 1,500 gallon capacity, provides the contractor, pig or poultry farmer a self-contained, high performance PTO pressure cleaner. This versatile unit can also be used for civil engineering projects, open-cast mining and a wide variety of tasks.



Access Ladder, Hatch & Low Level Filling Port
Allows easy tank filling and access

Unloader Valve
A proportional unloader valve and pressure gauge controls flow and indicates working pressure

Plunger Pump
A choice of triplex ceramic plunger pumps, with brass cylinder head and stainless valves provides long term reliability

Flexible Drive Coupling
The flexible drive coupling, fully guarded, absorbs excessive load protecting the pump

Locking Pin & Gun Holder
The locking pin controls rotation of the reel. The quick release coupling safely secures the gun during transport



PTO Drive Shaft
A PTO drive shaft and guard, supplied to the correct length, with a choice of 540 or 1,000 coupling

Optional Anti-freeze System
A fully recirculating anti-freeze system protects the pump and all pipework during winter periods

Lights
Full road lights to EC standards, fully enclosed to protect against damage

Manual Hose Reel
This 300ft capacity reel allows partial or full discharge and recovery of the hose during or after use, minimising hose damage and maximising labour efficiency

Model		6030	6050
Cleaning power	kW	19.1	19.1
Pump pressure	Bar/psi	205/3000	345/5000
Water volume	lt/gal/min	56/12.3	34/7.5
Engine	HP	28.9 min	28.9 min
Dimensions (mm)	LxWxH	6600x2350x2400	6600x2350x2400
Weight	kg	2650	2650
Water tank capacity	lt/gals	6800/1500	6800/1500